THE ACCELERATOR COMPARISON GUIDE

	ATS-SSBP-0	ATS-SSBP-1	ATS-SSBP-2	ATS-SSBP-0-U	ATS-SSBP-1-U	ATS-SSBP-2-U
Carrying Case	•	•	•	•	•	•
12V, 3A Input	•	•	•	•	•	•
12V, 2A Output	•	•	•	•	•	•
5V, 2A USB 2.0 Output	•	•	•	•	•	•
Li-Ion 7500 mAH	•	•	•	•	•	•
12.6V/94.5 Wh	•	•	•	•	•	•
4 Hour Recharge Time	•	•	•	•	•	•
10/100 LAN Input	•	•	•	•	•	•
24V, 1A PoE Output	•	•		•	•	
48V PoE Passive Output	•			•		
Leather Case with Straps		•	•		•	•
802.3af/at Output		•	•		•	•
10/100/1000 LAN Input		•	•		•	•
802.3af/at /bt (Types 3 & 4) Output			•			•
Up to20V, 5A USB C			•			•
1/4" Threaded Insert for DIY Mounting			•			•
Universal Adapter w/ Plugs for U.S., AUS, EUR and U.K.				•	•	•

The facts and figures herein are carefully compiled to the best of our knowledge and are intended for general informational purposes only. Responsibility for the use and application of AccelTex Solutions materials rests with the end user. All AccelTex Solutions products are sold pursuant to the AccelTex Solutions Terms and Conditions of Sale. © 2020 AccelTex Solutions. All Rights Reserved. AccelTex, AccelTex Solutions, the AccelTex Solutions Logo and other marks are trademarks or registered trademarks of AccelTex Solutions. Other products or service names may be the property of third parties.

1.888.406.8906 SALES@ACCELTEX.COM