802.3AF/AT/BT
65 WATT POE INJECTOR
ATS-65W-POE-INJ

MECHANICAL SPECIFICATIONS

Dimensions: 4.84” L x 2.36” W x 1.57” H (123 mm L x 60 mm W x 40 mm H)
Connector: 2 RJ-45 Jacks
LAN Port: 10/1000

ELECTRICAL SPECIFICATIONS

Input Voltage: AC 100-240V 50/60HZ
PoE Output Voltage: 52 VDC 1.25A
Max Load: 65 Watts
Comes with U.S. Line Cord
Upstream port lightning protection

ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor
Operating Temperature: 32 to 104°F (0 to 40°C)
Storage Temperature: -40 to 158°F (-40 to 70°C)
Operating Humidity: 10% to 90% RH (non-condensing)

LED INDICATORS

On: Power OK

The facts and figures herein are carefully compiled to the best of our knowledge and are intended for general informational purposes only. Responsibility for the use and application of AccelTex Solutions materials rests with the end user. All AccelTex Solutions products are sold pursuant to the AccelTex Solutions Terms and Conditions of Sale. © 2020 AccelTex Solutions. All Rights Reserved. AccelTex, AccelTex Solutions, the AccelTex Solutions Logo and other marks are trademarks or registered trademarks of AccelTex Solutions. Other products or service names may be the property of third parties.

1.888.406.8906
SALES@ACCELTEX.COM